

PRODUCT DESCRIPTION

Invisible Sealer gives advanced breathable protection for porous landscaping areas. Having excellent water and oil repelling properties, it protects against the main causes of degradation, helping to delay the ageing process.

Invisible Sealer is a non-film forming impregnating treatment. This means that the treated surface remains permeable to air and water vapour giving you superior protection that lasts.

This sealer is an environmentally friendly product, completely waterborne, non-toxic, solvent and silicone free.

CHEMICAL COMPOSITION

Invisible Sealer is a non-hazardous, waterborne fluoro-carbon resin based solution.

CHARACTERISTICS

- Delays the penetration of water and oily liquids allowing time to clean up an spillages to prevent staining of the hard landscaped area
- Virtually invisible
- Non-staining and non-yellowing
- Lasts up to 8 years if applied correctly and maintained, subject to trafficking and exposure to the elements
- A treated surface remains both air and water vapour permeable
- UV stable, does not degrade
- 95% + biodegradable according to OECD standards
- Non-hazardous

PACKAGING

5 litre (1.69floz) container.

TECHNICAL DATA

Physical State at 20°C	Liquid
Appearance	Clear/Straw
Odour	None
pH	7 ± 0.5
VOC	<0.0 g/l
Boiling Point	100°C
Density	1.0 Kg/L
Solubility in water	Fully soluble
Flash Point	N/A

COVERAGE

Coverage depends on the porosity of the material.

**1 Litre = 5m² to 10m²
(33.8floz = 54ft² to 107ft²)**

The figures indicated are approximate and should only be used as a general guideline.

STORAGE

Store in the original unopened container in a clean, dry area and ideally at 5°C - 25°C (41°F - 77°F). Use within 24 months from the date of manufacture.

CLEANING EQUIPMENT

Clean tools and equipment immediately after use with water.

APPLICATION

Not suitable if surfaces have been treated previously with a silicone or stearate-based water repellent.

Shake the container well before use.

Do not dilute or mix with another product.

Always carry out a test first to ensure the finished result is acceptable.

Ensure the surface to be treated is clean, dust-free and dry before applying Invisible Sealer.

Work in small areas when applying the Invisible Sealer as more than one coat may be required depending on how porous your paved area is.

The Invisible sealer is water based and the product must be impregnated until saturation is achieved. You must not let the Invisible Sealer dry between coats, this product needs to be applied before the first coat dries, wet on wet.

Apply with either a low pressure pump sprayer or brush.

Product will be touch dry within 1-6 hours, allowing longer in cold conditions.

Drying time 24 hours. For optimum results wait 5 to 7 days.

Do not apply during rain, frost, or when surface is <5°C and >25°C (<41°F and >77°F).

Please be aware darker coloured paving will have a considerable higher surface temperature in warmer weather conditions.

HEALTH AND SAFETY

Keep out of the reach of children. Avoid contact with skin.

Hand Protection Wear domestic gloves.

Skin Protection Not required.

Respiratory Protection Under normal conditions of use where there is adequate ventilation, no special respiratory protection equipment is needed.

Eye Protection If there is a real risk of splashing, wear protective goggles.

In case of ingestion Do not provoke vomiting. Contact a doctor or a specialist.